

Pergo Vinyl Underlay

Description:

- High quality underlay with sticky surface.
- Reduces impact sound to the bare minimum.
- Suitable for installation under vinyl click floors.
- Easy installation
- Perfect for floor heating/cooling.



Characteristics:

Product code	PGVUDL10	
Colour	Blue / Gold	
Shape	"Floor plank sized" plates joined together	
Thickness	1.5 mm	EN 823
Length	8500 mm	EN 822
Width	1180 mm	EN 822
Compression strength	300 kPa (30.6 ton / m ²)	EN 826
Fire protection classification	E _{fl}	EN 13501 – 1
Thermal conduction resistance	0.043 m ² ° K/W	DIN 4108
Deflection temp. under load	<70° C	ISO 140-8
Impact sound insulation	ΔL _w = 20dB ΔL _{lin} = 10dB	IHD 431
Walking noise reduction	-10%	

Installation instructions:

1. Unfold the underlay on the subfloor. Lay the underlay strips parallel to the laying direction of your Pergo® floor with the Pergo® logo on the top side. Do this strip by strip, as the laying of your floor progresses.
3. Install the following row next to the first. Seal the joints between the underlay with a damp-proof tape in order to keep the underlay in place.
4. Make sure the underlay fits together tightly (don't leave any gaps).

